



GruloFlat L

PVC flat hose, light weight

Lightweight layflat hose for delivery of liquids under pressure, flat rollable. Agricultural irrigation, construction industries, mining and industry in general.

Technical characteristics

Norm: ISO 1307

Temperature range: -5 °C to +60 °C | information valid for water

Standard Length: 100 m | further lengths on request

Colour: Blue

Construction

Cover: PVC, smooth

Reinforcement: Polyester yarn

Lining: PVC, seamless, black

Inner-Ø mm	Inner-Ø Inch	WP bar	BP bar	Weight/m kg	Article no.
32	1 1/4	6	18	0,190	10006-032
35	-	6	18	0,210	10006-035
38	1 1/2	5	15	0,225	10006-038
40	-	5	15	0,235	10006-040
45	-	5	15	0,265	10006-045
51	2	5	15	0,305	10006-052
60	-	4	12	0,355	10006-060
63	2 1/2	4	12	0,370	10006-063
70	-	4	12	0,420	10006-070
76	3	4	12	0,460	10006-076
80	-	4	12	0,495	10006-081
90	-	4	12	0,580	10006-090
102	4	4	12	0,650	10006-102
110	-	4	12	0,780	10006-110
127	5	3	9	1,000	10006-127
152	6	3	9	1,300	10006-153
204	8	2	6	2,050	10006-203

Reliable, for sure!