



GrüloDur

Rubber covered multipurpose hose

Flat hose for the delivery of liquid media - as well as hot water and compressed air. Hardwearing and abrasion resistant, robust and long-lasting. Resistance to oil, petrol and chemicals. Lightweight and very flexible compared to mandril built hoses.

Technical characteristics

Temperature range: -15 °C to +100 °C

Standard Length: 100 m | further lengths on request

Colour: Black

Construction

Cover: NBR/PVC compound, ribbed

Reinforcement: Polyester, circular woven

Lining: NBR/PVC compound, black

Inner-Ø mm	Inner-Ø Inch	Wall thickness mm	WP bar	BP bar	Weight/m kg	Article no.
25	1	1,95	30	90	0,250	10009-026
32	1 1/4	2,00	27	80	0,310	10009-032
38	1 1/2	1,95	21	62	0,345	10009-038
45	1 3/4	1,90	21	62	0,410	10009-045
52	2	2,00	20	60	0,460	10009-052
75	3	2,50	17	50	0,790	10009-075
90	3 1/2	2,35	17	45	0,930	10009-090
102	4	2,50	15	52	1,030	10009-102
110	4 1/3	2,40	15	45	1,160	10009-110
125	5	2,70	15	45	1,400	10009-125
152	6	2,60	14	42	1,650	10009-152
204	8	3,80	14	42	3,100	10009-204
254	10	3,90	10	30	4,000	10009-254

Reliable, for sure!