



## TRIX ROTSTRAHL®

### EPDM water hose - professional quality

**TRIX-ROTSTRAHL®** is the water hose for use in industry, local authorities, construction and civil engineering, landscape gardening, agriculture and many other applications. Thanks to its design and construction it is highly flexible and robust, ozone- and weather resistant. The ideal hose for cleaning and sprinkling, filling, spraying, rinsing and draining.

### Technical characteristics

**Temperature range:** -40 °C to +100 °C

**Standard Length:** 40 m

**Colour:** 6 red axially applied stripes on black cover

### Construction

**Cover:** EPDM, smooth | from DN 28 fabric-patterned

**Reinforcement:** Synthetic fibres

**Lining:** EPDM, non-porous, smooth

**Marking:** „Continental TRIX ROTSTRAHL® DN 13 PN 20 BAR / 290 PSI Made in Germany“

| Inner-Ø<br>mm | Inner-Ø<br>Inch | Wall thickness<br>mm | WP<br>bar | BP<br>bar | Bending radius<br>mm | Weight/m<br>kg | Article no. |
|---------------|-----------------|----------------------|-----------|-----------|----------------------|----------------|-------------|
| 13            | 1/2             | 3,30                 | 20        | 60        | 50                   | 0,245          | 10029-013   |
| 19            | 3/4             | 4,00                 | 20        | 60        | 65                   | 0,435          | 10029-019   |
| 25            | 1               | 4,50                 | 20        | 60        | 110                  | 0,580          | 10029-025   |
| 28            | 1 1/8           | 5,00                 | 15        | 45        | 120                  | 0,715          | 10029-028   |
| 30            | 1 3/16          | 5,50                 | 15        | 45        | 140                  | 0,835          | 10029-030   |
| 32            | 1 1/4           | 5,50                 | 15        | 45        | 170                  | 0,890          | 10029-032   |
| 35            | 1 3/8           | 5,50                 | 15        | 45        | 180                  | 0,940          | 10029-035   |
| 38            | 1 1/2           | 6,00                 | 15        | 45        | 200                  | 1,100          | 10029-038   |
| 40            | 1 9/16          | 6,00                 | 15        | 45        | 240                  | 1,150          | 10029-040   |
| 42            | 1 5/8           | 6,00                 | 10        | 30        | 250                  | 1,250          | 10029-042   |
| 50            | 2               | 7,00                 | 10        | 30        | 300                  | 1,565          | 10029-050   |

*Reliable, for sure!*