


TRICOFLEX

SUPER NOBELAIR®

Flexible Soft PVC air pressure hose

Three layer design, in extra flexible PVC, with high resistant polyester fibre reinforcement. Suitable for pneumatic tools, equipment of assembly workshops, wall mounted reels, carts and compressors.

Technical characteristics

Temperature range: -15 °C to +60 °C

Standard Length: 50 m

Colour: Sand-coloured

Construction

Cover: Soft-PVC

Reinforcement: Polyester fibre

Lining: Soft-PVC, black

Marking: SUPER NOBELAIR 20 BAR [Prod. No.]

Inner-Ø mm	Inner-Ø Inch	Wall thickness mm	WP bar	BP bar	Bending radius mm	Weight/m kg	Article no.
6,3	-	2,35	20	60	45	0,085	10035-006
7	-	2,50	20	60	49	0,090	10035-007
8	-	2,50	20	60	56	0,107	10035-008
9	-	2,75	20	60	63	0,132	10035-009
10	3/8	2,75	20	60	70	0,143	10035-010
12,7	1/2	3,15	20	60	89	0,205	10035-012
16	5/8	3,50	20	60	112	0,284	10035-016
19	3/4	3,75	20	60	145	0,352	10035-019
25	1	4,25	20	60	210	0,515	10035-025

All technical information refer to a temperature of 20 °C.

Reliable, for sure!