



GrünLine

GrüloSaug PVC suction hose

High flexible and strong PVC-spiral hose for irrigation, delivery of water, fertilizers, acids, detergents, solutions and for well pump.

Technical characteristics

Temperature range: -5 °C to +60 °C

Standard Length: 50 m | from DN 110: 25 m

Colour: Green transparent with white spiral

Construction

Cover: Soft-PVC

Reinforcement: Hard PVC spiral

Lining: PVC, smooth

Inner-Ø mm	Inner-Ø Inch	Wall thickness mm	WP bar	Vacuum bar	Bending radius mm	Weight/m kg	Article no.
19	3/4	2,4	7	0,60	80	0,200	10046-019
25	1	2,5	7	0,60	110	0,250	10046-025
32	1 1/4	2,8	7	0,60	140	0,320	10046-032
35	-	3,0	6	0,60	150	0,380	10046-035
38	1 1/2	3,2	6	0,60	180	0,420	10046-038
40	-	3,3	6	0,60	190	0,470	10046-040
45	1 3/4	3,3	5	0,60	220	0,530	10046-045
50	2	3,4	5	0,60	240	0,640	10046-050
63	2 1/2	3,5	5	0,60	290	0,810	10046-063
76	3	4,0	4	0,60	370	1,150	10046-075
80	-	4,1	4	0,70	400	1,300	10046-080
90	-	4,4	4	0,60	450	1,560	10046-090
100	4	4,7	4	0,60	500	1,710	10046-100
110	-	6,0	4	0,70	530	2,100	10046-110
125	-	6,7	3	0,70	690	2,900	10046-125

All technical information refer to a temperature of 20 °C.

Reliable, for sure!