



## GrüloVin L

### PVC Suction hose, transparent

Robust, flexible and abrasion resistant PVC hose, usable as suction hose for water, food, beverages to 28 Vol.-% of alcohol, potable water, for vacuum pumps and for groundwater drawdown. Very good chemical resistance.

## GrüloLine

### Technical characteristics

**Temperature range:** -5 °C to +65 °C

**Standard Length:** 50 m

**Colour:** Transparent

### Construction

**Cover:** Soft-PVC, smooth

**Reinforcement:** Embedded steel wire spiral

**Lining:** Soft-PVC, smooth

Inner-Ø mm	Inner-Ø Inch	Wall thickness mm	WP bar	Vacuum bar	Bending radius mm	Weight/m kg	Article no.
12	-	3,10	12	0,90	36	0,186	10048-012
13	1/2	3,10	12	0,90	39	0,206	10048-013
16	5/8	3,10	12	0,90	48	0,225	10048-016
19	3/4	3,50	11	0,90	57	0,320	10048-019
22	7/8	3,70	10	0,90	66	0,398	10048-022
25	1	4,00	10	0,90	75	0,506	10048-025
30	-	4,20	9	0,90	90	0,610	10048-030
32	1 1/4	4,20	9	0,90	96	0,640	10048-032
50	2	5,40	7	0,90	150	1,260	10048-050
75	3	6,70	5	0,90	225	2,230	10048-075
80	-	6,30	4	0,90	240	2,426	10048-080
102	4	7,50	3	0,90	306	3,640	10048-102
152	6	10,00	2	0,90	456	6,300	10048-152

All technical information refer to a temperature of 20 °C.

*Reliable, for sure!*