

**MERLETT****Vacupress® Flex****TPE suction and discharge hose**

Even at temperatures below 0 °C highly flexible all-purpose hose for discharge and suction of liquids and lightly abrasive media like cement. Good weather- and abrasion resistance. Due to its outstanding flexibility **Vacupress® Flex** ideally suited as suction and discharge hose for sewer cleaning vehicles and silo trucks. Also with white tube / for food available.

Technical characteristics**Temperature range:** -25 °C to +60 °C**Standard Length:** 60 m | from DN 38: 30 m, from DN 127: 20 m**Colour:** Black**Construction****Cover:** PVC, smooth**Reinforcement:** Embedded steel wire spiral, polyester yarn**Lining:** PVC, black, smooth

Inner-Ø mm	Inner-Ø Inch	Outer-Ø mm	WP bar	BP bar	Vacuum bar	Bending radius mm	Weight/m kg	Article no.
19	3/4	28,0	20	60	0,90	70	0,475	10053-019
25	1	35,5	16	48	0,90	80	0,680	10053-025
30	-	40,5	16	48	0,90	90	0,770	10053-030
32	1 1/4	42,5	16	48	0,90	100	0,800	10053-032
35	1 3/8	48,0	14	42	0,90	115	1,100	10053-035
38	1 1/2	51,0	14	42	0,90	125	1,200	10053-038
40	-	53,0	14	42	0,90	130	1,220	10053-040
45	1 3/4	58,0	12	36	0,90	140	1,400	10053-045
50	2	64,0	12	36	0,90	150	1,600	10053-050
60	-	74,0	12	36	0,90	180	2,000	10053-060
63	2 1/2	77,0	12	36	0,90	190	2,100	10053-063
75	-	91,0	12	36	0,90	190	2,950	10053-075
76	3	92,0	12	36	0,90	210	2,970	10053-076
80	-	96,0	10	30	0,90	220	3,020	10053-080
90	3 1/2	107,0	10	30	0,90	250	3,500	10053-090
100	-	117,0	10	30	0,90	300	4,050	10053-100
102	4	119,0	10	30	0,90	300	4,150	10053-102
120	-	138,0	8	24	0,90	350	5,430	10053-120
127	5	148,0	7	22	0,90	370	5,950	10053-127
152	6	171,0	5	15	0,90	480	7,050	10053-152

Reliable, for sure!