



APD Petzeftakis
Schlauchtechnik

Super Heliflex

PVC-BUNA suction- and discharge hose

This suction and discharge hose can be used for sprinkling, cesspool- and canal cleaning purposes as well as for liquid manure hoses in agriculture. **Super Heliflex** is ozon- and UV resistant, dimensionally stable, interiorly smooth and highly flexible due to its special plastic recipe.

Technical characteristics

Temperature range: -40 °C to +60 °C

Standard Length: 50 m | DN 127: 25 m, DN 152: 20 m

Colour: Silver-grey with white spiral

Construction

Cover: PVC/BUNA

Reinforcement: Hard-PVC spiral

Lining: PVC/BUNA, smooth

Inner-Ø mm	Inner-Ø Inch	Outer-Ø mm	Wall thickness mm	WP bar	Vacuum bar	Bending radius mm	Weight/m kg	Article no.
25	1	33,4	4,2	7	0,9	110	0,500	10072-025
32	1 1/4	41,0	4,6	6	0,9	120	0,600	10072-032
38	1 1/2	48,0	5,0	6	0,9	140	0,700	10072-038
40	-	50,0	5,0	5	0,9	150	0,835	10072-040
51	2	61,4	5,2	5	0,9	170	1,000	10072-051
60	-	71,0	5,5	4	0,9	190	1,300	10072-060
63	2 1/2	74,0	5,5	4	0,9	210	1,400	10072-063
76	3	88,4	6,2	4	0,9	240	1,700	10072-076
80	-	92,2	6,2	3	0,9	250	2,100	10072-080
90	-	102,0	6,0	3	0,9	290	2,210	10072-090
102	4	116,4	7,2	3	0,9	320	2,700	10072-100
127	5	143,0	8,0	2	0,9	620	3,600	10072-127
152	6	170,0	9,0	2	0,9	680	5,000	10072-152
203	8	227,0	12,00	1	0,9	1100	8,510	10072-203

All technical information refer to a temperature of 20 °C.

Reliable, for sure!