



Acetylen ISO 3821 red

Acetylene welding hose

Highly flexible, kink-resistant acetylene welding hose, which meets ISO 3821 requirements. For applications in welding shops. Ozone and UV resistant.

Technical characteristics

Norm: ISO 3821

Temperature range: -30 °C to +70 °C

Standard Length: 50 m, 100 m

Colour: Red

Construction

Cover: SBR/EPDM, serrated

Reinforcement: High tensile synthetic textile

Lining: SBR, black, smooth

Inner-Ø mm	Inner-Ø Inch	Wall thickness mm	WP bar	BP bar	Bending radius mm	Weight/m kg	Article no.
4,0	-	3,50	20	60	32	0,120	10107-004
5,0	-	3,00	20	60	40	0,150	10107-005
6,3	1/4	3,50	20	60	50	0,190	10107-006
8,0	-	3,50	20	60	65	0,230	10107-008
9,0	-	3,50	20	60	75	0,250	10107-009
10,0	3/8	3,50	20	60	80	0,270	10107-010
13,0	1/2	5,00	20	60	110	0,375	10107-013
16,0	-	5,00	20	60	130	0,540	10107-016
19,0	3/4	6,00	20	60	150	0,670	10107-019
25,0	1	5,50	20	60	200	0,870	10107-025

Reliable, for sure!