



GrüloLine

GrüloTank SP

Tank truck hose with spiral

Tank truck hose with spiral according EN 12115. Suitable for hydrocarbons with max. 55% aromatic contents, Diesel and Fuel. Oil, weather and ozone resistant cover. Electrically conductive ($R \leq 106 \Omega/m$).

Technical characteristics

Norm: EN 12115

Temperature range: -30 °C to +80 °C

Standard Length: 40 m

Colour: Black

Construction

Cover: CR

Reinforcement: Synthetic textile with double steel spiral and two copper litz wires

Lining: NBR, black, smooth

Marking: GrüloTank SP EN 12115 BD 16 bar

Inner-Ø mm	Inner-Ø Inch	Outer-Ø mm	WP bar	Vacuum bar	Bending radius mm	Weight/m kg	Article no.
19	3/4	31	16	0,90	114	0,720	10191-19
25	1	37	16	0,90	150	0,800	10191-025
32	1 1/4	44	16	0,90	160	0,980	10191-032
38	1 1/2	51	16	0,90	228	1,140	10191-038
50	2	65	16	0,90	310	1,690	10191-050
76	3	91	16	0,90	460	2,830	10191-076
102	4	118	16	0,90	620	3,950	10191-102

Reliable, for sure!