

IMPROVED
FORMULA

GrüloLine

GrüloElastic SE**Medium and heavy duty PVC suction and discharge hose**

GrüloElastic SE is a suction and discharge hose for irrigation, sink- and canal cleaning as well as for agricultural purposes as a slurry hose. It is weatherproof, dimensionally stable and smooth inside. Due to its special synthetic formula, **GrüloElastic SE** stays flexible even at temperatures below zero.

Technical characteristics**Temperature range:** -20 °C to +60° C**Standard Length:** 50 m | from DN 110: 30 m, DN 152: 20 m**Colour:** Grey**Construction****Cover:** PVC/BUNA, slightly wavy**Reinforcement:** Hard-PVC spiral, impact and pressure resistant**Lining:** PVC/BUNA, smooth

Inner-Ø mm	Inner-Ø Inch	Outer-Ø mm	WP bar	Vacuum bar	Bending radius mm	Weight/m kg	Article no.
32	1 1/4	41,0	6	0,90	123	0,600	10201-032
35	-	44,0	6	0,90	132	0,660	10201-035
38	1 1/2	48,0	6	0,90	144	0,700	10201-038
45	-	55,5	5	0,90	167	0,900	10201-040
51	2	61,8	5	0,90	185	1,070	10201-051
63	2 1/2	75,0	4	0,90	263	1,400	10201-063
76	3	89,0	4	0,90	312	1,720	10201-076
80	-	93,0	3	0,90	326	1,900	10201-080
90	-	104,0	3	0,90	364	2,250	10201-090
100	4	116,0	3	0,90	406	2,630	10201-100
110	-	126,0	3	0,90	504	3,100	10201-110
127	5	144,0	2	0,90	576	3,900	10201-127
152	6	170,0	2	0,90	680	5,000	10201-152

All technical information refer to a temperature of 20 °C.

Reliable, for sure!