



## GrüloVent

### PVC suction hose, flame retardant

Medium weight and flexible PVC ducting hose with rigid PVC spiral for suction of air, fumes and dust, cable protection, discharging of liquids. Flame retardant acc. to UL94 V2.

#### Technical characteristics

**Norm:** UL94 V0

**Temperature range:** -5 °C to +60 °C

**Standard Length:** 25 m | from DN 110: 10 m

**Colour:** Grey

#### Construction

**Cover:** PVC, corrugated

**Reinforcement:** Hard PVC spiral

**Material:** Soft PVC, smooth

Inner-Ø mm	Material thickness mm	WP bar	Vacuum bar	Bending radius mm	Weight/m kg	Article no.
51	0,90	1,30	0,50	75	0,410	10214-051
76	1,00	1,10	0,40	113	0,700	10214-076
80	1,00	1,00	0,40	120	0,730	10214-080
90	1,00	1,00	0,40	135	0,780	10214-090
100	1,00	1,00	0,40	150	0,980	10214-100
110	1,00	0,90	0,40	165	1,100	10214-110
120	1,00	0,70	0,35	180	1,280	10214-120
127	1,00	0,70	0,35	188	1,300	10214-127
152	1,10	0,50	0,35	225	1,700	10214-152
160	1,20	0,50	0,35	240	1,820	10214-160
200	1,30	0,30	0,30	300	2,170	10214-200
250	1,50	0,30	0,30	375	3,400	10214-250
280	1,50	0,30	0,25	390	3,500	10214-280
300	1,50	0,30	0,20	400	3,600	10214-300

All technical information refer to a temperature of 23 °C.

*Reliable, for sure!*