



GrüloLine

GrüloPren 1

Light spiral hose made of neoprene

Lightweight spiral hose for suction and transport of hot gases and vapors. **GrüloPren 1** find its use mainly in the plastics industry as well as in vehicle and engine construction and has a very good flexibility and chemical resistance.

Technical characteristics

Temperature range: -55 °C to +120 °C

Standard Length: 10 m, 15 m

Colour: Black

Construction

Material: Neoprene® coated polyester fabric,
1-ply with white glass cord and wire insert

Inner-Ø mm	Wall thickness mm	WP bar	Vacuum bar	Bending radius mm	Weight/m kg	Article no.
50	0,40	0,80	0,20	50	0,300	10218-050
60	0,40	0,80	0,16	60	0,360	10218-060
70	0,40	0,70	0,14	70	0,420	10218-070
75	0,40	0,60	0,10	75	0,450	10218-075
80	0,40	0,60	0,09	80	0,500	10218-080
100	0,40	0,50	0,08	100	0,570	10218-100
125	0,40	0,50	0,07	125	0,710	10218-125
140	0,40	0,30	0,06	140	0,790	10218-140
150	0,40	0,20	0,06	150	1,010	10218-150
175	0,40	0,20	0,05	175	1,180	10218-175
200	0,40	0,20	0,04	200	1,200	10218-200
250	0,40	0,15	0,03	250	1,250	10218-250
300	0,40	0,10	0,02	300	1,390	10218-300

All technical information refer to a temperature of 23 °C.

Reliable, for sure!