



## GrüloLine

### GrüloVin

#### PVC suction hose, transparent

Robust, flexible and abrasion resistant PVC hose, usable as a suction hose for water, foodstuff, beverages to 28 Vol.-% of alcohol, potable water, for vacuum pumps and to the drawdown. Very good chemical resistance.

#### Technical characteristics

**Temperature range:** -5 °C to +60 °C

**Standard Length:** 30 m

**Colour:** Green transparent

#### Construction

**Cover:** Soft PVC, smooth

**Reinforcement:** Embedded steel wire spiral

**Lining:** Soft PVC, smooth

Inner-Ø mm	Inner-Ø Inch	WP bar	BP bar	Vacuum bar	Bending radius mm	Weight/m kg	Article no.
20	3/4	5	15	0,90	50	0,340	10248-020
22	7/8	5	15	0,90	55	0,360	10248-022
25	1	5	15	0,90	60	0,510	10248-025
30	-	4	13	0,90	70	0,600	10248-030
32	1 1/4	4	13	0,90	75	0,650	10248-032
38	1 1/2	4	12	0,90	90	0,800	10248-038
40	-	3	9	0,90	95	0,870	10248-040
45	1 3/4	3	9	0,80	105	1,100	10248-045
51	2	3	9	0,80	125	1,200	10248-050
60	-	2	7	0,70	135	1,800	10248-060
63	2 1/2	2	7	0,70	150	1,950	10248-063
70	-	2	6	0,70	180	2,200	10248-070
76	3	2	6	0,70	195	2,500	10248-075
80	-	2	6	0,70	220	2,700	10248-080
90	3 1/2	2	6	0,60	260	3,000	10248-090
102	4	2	6	0,60	300	3,400	10248-102
127	5	2	6	0,60	385	4,700	10248-125
152	6	2	6	0,60	460	6,350	10248-152

All technical information refer to a temperature of 20 °C.

Reliable, for sure!