



TRIX® oxyacetylene hose

For the safe transport of oxygen

TRIX® oxyacetylene hoses blue are designed for the transport of oxygen. They comply with the latest ISO 3821 standards and offers the highest possible safety standard

Applications: Construction, vehicle construction, foundries, structural and civil engineering, steel construction and many more.

Technical characteristics

Norm: EN ISO 3821

Temperature range: -40 °C to +60 °C

Standard Length: 40 m

Colour: Blue

Construction

Cover: EPDM, smooth, abrasion resistant, ozone-, weather and UV resistant

Reinforcement: Synthetic fibres

Lining: EPDM, black, smooth, non-porous, electrically conductive $R \leq 10^6 \Omega/m$

Marking: Continental ContiTech TRIX®-AUTOGEN DN 9 x 19
DIN EN ISO 3821 2MPa (20 bar / 290PSI) Made in Germany

Inner-Ø mm	Inner-Ø Inch	Wall thickness mm	WP bar	BP bar	Bending radius mm	Weight/m kg	Article no.
4,00	1/6	3,50	20	60	15	0,130	10313-004-003,5
6,30	1/4	3,50	20	60	25	0,170	10313-006,3-003,5
6,30	1/4	5,00	20	50	20	0,260	10313-006,3-005
9,00	3/8	5,00	20	60	30	0,330	10313-009-005,5
11,00	7/16	5,00	20	60	35	0,370	10313-011-005
12,50	1/2	5,00	20	60	45	0,400	10313-012,5-005
16,00	5/8	6,00	20	60	55	0,600	10313-016-006

Pressure data referring to room temperature.

Reliable, for sure!