



CompoCHEM 10 SSE

Composite hose for chemicals

CompoCHEM 10 SSE is suitable as suction and discharge hose for the transfer of chemicals, such as loading and unloading of tank trucks in industry plants and marine applications. Suitable for chemical products such as acids, fatty acids, alkalis and solvents, even in corrosive environments.

Also available in other versions.

Technical characteristics

Norm: EN 13765:2010

Temperature range: -30 °C up to +100 °C

Standard Length: max. 30 m

Safety factor: 5:1

Colour: Blue

Construction

Cover: PVC coated polyester fabric

Inner wire spiral: Stainless steel

Outer wire spiral: Stainless steel

Lining: Polypropylene

| Inner-Ø mm | Inner-Ø Inch | WP bar | BP bar | Bending radius mm | Weight/m kg | Article no. |
|---------------|-----------------|-----------|-----------|----------------------|----------------|-------------|
| 51 | 2 | 10 | 50 | 190 | 2,160 | 10325-051 |
| 65 | 2 1/2 | 10 | 50 | 225 | 2,830 | 10325-065 |
| 76 | 3 | 10 | 50 | 290 | 3,670 | 10325-076 |
| 102 | 4 | 10 | 50 | 320 | 5,710 | 10325-102 |

Reliable, for sure!