



Grülo TX 40

Delivery hose 40° shore

Delivery hose for over- and low pressure with armoring from woven fabric inlay and completely embedded steel wire. Smooth cover with a fabric texture ensures good resistance to wear and weather. Thick, smooth-walled wear tubes provide low resistance to flow and extremely long durability. **Grülo TX 40** is suitable for slurry with particle size less than 10 mm.

Technical characteristics

Temperature range: -30 °C to +70 °C

Standard Length: 20 m | from DN 152: 10 m

Colour: Black

Construction

Cover: SBR, fabric impressions

Reinforcement: Steel wire spiral galvanized, textile woven fabric reinforcement

Lining: Tribological hose 40° Shore

Inner-Ø mm	Inner-Ø Inch	Wall thickness mm	WP bar	BP bar	Vacuum bar	Bending radius mm	Weight/m kg	Article no.
51	2	9,50	10	30	0,90	150	2,400	10340-051
80	-	11,00	10	30	0,90	210	4,400	10340-080
102	4	11,00	10	30	0,90	280	5,800	10340-102
127	5	13,50	10	30	0,90	400	8,400	10340-127
152	6	13,00	10	30	0,90	600	9,500	10340-152
204	8	17,00	10	30	0,90	1300	15,200	10340-204
254	10	18,50	5	15	0,50	1600	20,800	10340-254
355	14	23,00	5	15	0,50	2200	40,800	10340-355

Reliable, for sure!