



SUPERFLEX PU PLUS HMR

PU suction hose

The **SUPERFLEX PU PLUS HMR** is a light to medium weight ester polyurethane hose with an embedded copper plated steel spiral. It has a high abrasion resistance and is particularly suitable for suction of dust, pellets, and granulates.

GrüloLine

Technical characteristics

Norm: ISO 291

Approval: FDA 21 CFR 177.1680 for dry foods

Temperature range: -40 °C to +90 °C

Standard Length: 20 m | from DN 100: 15 m, from DN 150: 10 m

Colour: Transparent

Construction

Material: Polyurethane, copper plated steel spiral

Inner-Ø mm	Outer-Ø mm	Material thick- ness mm	WP bar	Vacuum bar	Bending radius mm	Weight/m kg	Article no.
50	60	1,40	2,2	0,80	100	0,620	10411-050
76	86	1,45	1,5	0,50	150	1,000	10411-076
100	111	1,50	1,1	0,40	200	1,350	10411-100
127	138	1,50	0,9	0,30	260	1,800	10411-127
150	161	1,50	0,8	0,30	300	2,050	10411-150
160	171	1,50	0,8	0,20	320	2,200	10411-160
200	217	1,60	0,6	0,20	400	3,200	10411-200

Reliable, for sure!