

**MERLETT****Vacupress® Oil****Flexible PVC-hose with steel spiral, 2-ply**

Two-layer hose in thermoplastic PVC with embedded galvanized steel spiral and polyester yarn reinforcement for the delivery and suction of hydraulic oils and fuels. From DN 76 with cover in PU. Highly flexible and a good abrasion resistance.

Technical characteristics

Norm: ISO 4649, ISO 291

Temperature range: -25 °C to +55 °C

Standard Length: DN 25: 60 m, from DN 38: 40m

Colour: Black

Construction

Cover: Polyurethane, abrasion resistant

Reinforcement: Polyester yarn, steel wire helix

Lining: PVC/polyurethane rubber compound

Inner-Ø mm	Inner-Ø Inch	Wall thickness mm	WP bar	BP bar	Vacuum bar	Bending radius mm	Weight/m kg	Article no.
25	1	5,25	16	48	0,90	80	0,670	10428-025
38	1 1/2	6,50	14	42	0,90	125	1,200	10428-038
45	1 3/4	6,50	12	36	0,90	140	1,340	10428-045
50	2	7,00	12	36	0,90	150	1,730	10428-050
60	-	7,00	12	36	0,90	180	1,950	10428-060

All technical information refer to a temperature of 20 °C.

Reliable, for sure!