



GruloPren 2

Lightweight spiral hose made of neoprene®, 2-ply

Highly flexible, two-ply spiral hose made of Neoprene®-coated polyester fabric with good chemical resistance and low temperature flexibility. It is used mainly used for the extraction of hot hot air, gases and vapours.

Technical characteristics

Temperature range: -55 °C bis +120 °C

Standard Length: 10 m, 15 m

Colour: Black

Construction

Material: Neoprene® coated polyester fabric,
2-ply with white glass cord and wire insert

Inner-Ø mm	Wall thickness mm	WP bar	Vacuum bar	Bending radius mm	Weight/m kg	Article no.
60	0,80	1,00	0,20	90	0,490	10493-060
70	0,80	0,90	0,18	105	0,570	10493-070
75	0,80	0,85	0,12	113	0,610	10493-075
80	0,80	0,80	0,10	120	0,650	10493-080
100	0,80	0,60	0,08	153	0,720	10493-100
125	0,80	0,50	0,07	190	0,900	10493-125
140	0,80	0,40	0,06	210	1,010	10493-140
150	0,80	0,30	0,06	230	1,220	10493-150
175	0,80	0,25	0,05	270	1,430	10493-175
200	0,80	0,20	0,04	305	1,630	10493-200
250	0,80	0,15	0,03	380	2,040	10493-250
300	0,80	0,10	0,02	460	3,000	10493-300

Reliable, for sure!