



## GrüloKan 250 Inliner

With polyamide inliner

**GrüloKan 250 Inliner** offers you - besides all the advantages of a common rubber sewer cleaning hose - an extremely smooth polyamide inliner, which guarantees an obviously lower pressure drop. This minimisation of the pressure drop leads to a reduction of the engine speed which means considerable savings in fuel costs. This offers an efficiency benefit you should not miss! **GrüloKan 250 Inliner** is recommended especially for water conditioning and water recycling vehicles.

All hoses are assembled with BSP female/male and ferrules. Delivery takes place with test certificate on each assembled hose.

### Technical characteristics

**Temperature range:** -40 °C to +70 °C

**Standard Length:** 60 m, 80 m, 120 m, 160 m, 180 m, 200 m, 240 m  
further lengths on request

**Availability:** 10 m up to 240 m

**Colour:** Black

### Construction

**Cover:** NR/SBR, highly abrasion resistant, smooth

**Reinforcement:** 2-ply braided synthetic fibres

**Inliner:** Polyamide, white

**Lining:** NR/SBR, black, smooth

**Marking:** Transfer tape G+L Ellipse GrüloKan Inliner 250 bar DN [..]

Inner-Ø mm	Inner-Ø Inch	Wall thickness mm	WP bar	BP bar	Bending radius mm	Weight/m kg	Article no.
25	1	7,00	250	625	100	0,830	10666-025

*Reliable, for sure!*