



GrüloFood Flex

PU spiral hose

Light weight and permanently antistatic PU-spiral hose with stainless steel wire. **GrüloFood Flex** is highly flexible, resistant to hydrolysis and microbes, non toxic and food proved according to FDA and EU-regulations. It is especially suitable for suction of air, dust and fibres in food and pharmaceutical industries.

Technical characteristics

Approval: EG 1935/2004, EU 10/2011
FDA 21 CFR 177.2600 / 178.2010, TRBS 2153

Temperature range: -40 °C to +100 °C

Standard Length: 10 m, 15 m

Colour: Transparent

Construction

Material: Polyether- polyurethane with stainless steel wire, permanently antistatic

Inner-Ø mm	Material thickness mm	WP bar	Vacuum bar	Bending radius mm	Weight/m kg	Article no.
50	0,40	0,40	0,20	35	0,270	10711-050
60	0,40	0,40	0,16	42	0,310	10711-060
70	0,40	0,35	0,14	49	0,360	10711-070
75	0,40	0,30	0,10	53	0,390	10711-075
80	0,40	0,28	0,10	56	0,410	10711-080
100	0,40	0,20	0,09	70	0,530	10711-100
120	0,40	0,20	0,08	85	0,630	10711-120
125	0,40	0,20	0,08	88	0,660	10711-125
140	0,40	0,15	0,06	95	0,730	10711-140
150	0,40	0,10	0,06	105	0,780	10711-150
175	0,40	0,09	0,05	123	0,910	10711-175
200	0,40	0,08	0,05	140	1,110	10711-200
225	0,40	0,06	0,04	160	1,240	10711-225
250	0,40	0,05	0,03	175	1,380	10711-250
300	0,40	0,03	0,03	210	1,650	10711-300
350	0,40	0,02	0,02	245	2,210	10711-350
400	0,40	0,02	0,02	280	2,520	10711-400
450	0,40	0,01	0,01	315	2,830	10711-450
500	0,40	0,01	0,01	350	2,140	10711-500
600	0,40	0,01	0,01	400	4,570	10711-600

All technical information refer to a temperature of 23 °C.

Reliable, for sure!