



GrüloLine

GrüloKan 250 Premium

Outstanding abrasion resistance

GrüloKan 250 Premium offers you much more than all common rubber sewer cleaning hoses. The especially developed composite bi-layers structure of the cover enables a very high abrasion resistance according to EN ISO 6945 (50 N and 2000 cycles max. 1g). This guarantees you a long lifetime at equal flexibility in comparison to our classic **GrüloKan 250**. Therefore our **GrüloKan 250 Premium** can be used in any situation, where all others fail.

All hoses are assembled with BSP female/male and ferrules. Delivery takes place with test certificate on each assembled hose.

Technical characteristics

DIN: EN ISO 6945

Temperature range: -40 °C to + 70 °C

Standard Length: 60 m, 80 m, 120 m, 160 m, 180 m, 200 m, 220 m, 240 m
further lengths on request

Availability: 10 m up to 240 m | DN 32 up to 200 m

Colour: Black

Construction

Cover: Composite bi-layers structure with outstanding abrasion resistance

Reinforcement: Twofold braided synthetic fibres

Lining: NR/SBR, black, smooth

Marking: Transfer tape G+L Ellipse GrüloKan Premium 250 bar DN [..]

Inner-Ø mm	Inner-Ø Inch	Wall thickness mm	WP bar	BP bar	Bending radius mm	Weight/m kg	Article no.
25	1	7,00	250	625	110	0,775	10866-025
32	1 1/4	8,00	250	625	140	1,095	10866-032

Reliable, for sure!