



## GrüloAir AS-HL

### Antistatic PVC air ducting hose

Light and highly flexible antistatic PVC spiral hose for suction of paint and solvent fumes as well as for air-conditioning and dust in Ex-endangered areas. **GrüloAir AS-HL** has a fire-resistant wall according to DIN 4102 B1 and a good compressibility and low temperature flexibility. An outer yellow wearstrip profile is a good heavy protection. **GrüloAir AS-HL** is available with spiral-free expiring foil or with welded end rings.

### Technical characteristics

**DIN:** DIN 4102 B1

**Approval:** TRBS 2153

**Temperature range:** -20 °C to +70 °C

**Standard Length:** 5 m, 7,5 m, 10 m

**Colour:** Black

### Construction

**Material:** PVC-coated-polyester fabric and wire insert, antistatic  $R \leq 10^8 \Omega/m$

Inner-Ø mm	Material thickness mm	WP bar	Vacuum bar	Bending radius mm	Weight/m kg	Article no.
150	0,45	0,64	0,05	105	1,100	11014-150
200	0,45	0,55	0,05	140	1,200	11014-200
250	0,45	0,45	0,03	175	1,350	11014-250
300	0,45	0,35	0,03	210	1,440	11014-300
400	0,45	0,25	0,03	280	2,050	11014-400
500	0,45	0,20	0,03	350	3,300	11014-500
600	0,45	0,17	0,02	420	4,500	11014-600
700	0,45	0,15	0,02	490	5,600	11014-700
800	0,45	0,13	0,01	560	6,800	11014-800
900	0,45	0,11	0,01	630	8,400	11014-900
1000	0,45	0,10	0,01	700	10,000	11014-1000

Reliable, for sure!