



## GrüloAir PS-L PVC air ducting hose

Highly flexible and very lightweight PVC hot air hose, which is particularly suitable for air conditioning, ventilation and suction of asbestos and dust. **GrüloAir PS-L** is axially compressible and has a good low temperature flexibility. Due to its flame-retardant wall according to DIN 4102 B1 the spiral hose can also be used for heating of tents and buildings. In addition, an outer wearstrip profile offers good abrasion protection and make the hose highly resistant to aging. **GrüloAir PS-L** is available with spiral free expiring foil or with welded end rings.

### Technical characteristics

**DIN:** DIN 4102 B1

**Temperature range:** -20 °C to +80 °C

**Standard Length:** 5 m, 7,5 m, 10 m

**Colour:** Yellow

### Construction

**Material:** PVC-coated-polyester fabric and wire insert

Inner-Ø mm	Material thickness mm	WP bar	Vacuum bar	Bending radius mm	Weight/m kg	Article no.
150	0,25	0,35	0,05	105	0,500	11015-150
200	0,25	0,30	0,05	140	0,680	11015-250
250	0,25	0,22	0,03	175	0,850	11015-200
300	0,25	0,18	0,03	210	1,000	11015-300
400	0,25	0,14	0,03	280	1,600	11015-400
500	0,25	0,10	0,03	350	2,000	11015-500
600	0,25	0,08	0,02	420	2,400	11015-600
700	0,25	0,07	0,02	490	2,800	11015-700
800	0,25	0,06	0,01	560	3,200	11015-800
900	0,25	0,05	0,01	630	3,600	11015-900
1000	0,25	0,05	0,01	700	4,000	11015-1000

Reliable, for sure!