



## GruloFlex PUR M

### PU ducting hose for medium duty applications

Moderate weight and flexible polyurethane spiral hose for suction and discharging of abrasive granules with a material thickness of 1,4 mm. **GruloFlex PUR-M** is resistant to oil and petrols, non toxic and food proved according to FDA and EU-regulations. It is free of halogen and softeners with an excellent abrasion resistance.

#### Technical characteristics

**Approval:** FDA, EU-regulations

**Temperature range:** -40 °C to +100 °C

**Standard Length:** 10 m, 15 m

**Colour:** Transparent

#### Construction

**Material:** Polyether-polyurethane with copper plated steel wire helix

Inner-Ø mm	Material thickness mm	WP bar	Vacuum bar	Bending radius mm	Weight/m kg	Article no.
50	1,40	1,90	0,60	75	0,670	11033-050
75	1,40	1,20	0,50	113	0,980	11033-075
100	1,40	1,10	0,40	150	1,360	11033-100
125	1,40	0,80	0,25	188	1,540	11033-125
150	1,40	0,70	0,20	225	1,820	11033-150
200	1,40	0,50	0,15	300	2,920	11033-200
250	1,40	0,30	0,10	375	3,570	11033-250

All technical information refer to a temperature of 25 °C.

Reliable, for sure!