


SEMPERIT 

Resist P FEP

Premium FEP chemical hose

Premium chemical hose with teflon lining, suitable for transporting nearly all chemicals used in the chemical industry. Furthermore **Resist P FEP** convinces by its high temperature resistance: depending on discharge medium up to +150 °C, steam cleaning, without pressure, up to 130 °C / max. 30 min. Cover is electrically conductive ($R \leq 106 \Omega/m$).

Technical characteristics

Norm: EN 12115:2011, TRbF 131/2:1992

Temperature range: -20 °C to +150 °C | depending on discharge medium

Standard Length: 40 m | from DN 75: 20 m

Colour: Black

Construction

Cover: CR, cloth impression

Reinforcement: Textile wrapped, 2 copper wires, zinc plated steel wire helix

Lining: FEP, smooth, isolating

Marking: SEMPERIT S Resist-P-Chemie FEP

Inner-Ø mm	Inner-Ø Inch	Wall thickness mm	WP bar	Bending radius mm	Weight/m kg	Article no.
25	1	6,0	16	225	0,900	11162-025
38	1 1/2	6,5	16	340	1,350	11162-038
50	2	8,0	16	415	1,900	11162-050
75	-	8,0	16	525	3,250	11162-075

Reliable, for sure!