



GrüloLine

GrüloSaug SE PVC slurry hose

GrüloSaug SE is a highly flexible, pressure and abrasion resistant PVC hose for lightweight applications in agriculture, industry and sewerage. It is particularly suitable for the loading and unloading of water, light chemicals and abrasive media. Due to its reinforcement spiral of impact and pressure resistant plastic the **GrüloSaug SE** is extremely durable. In addition **GrüloSaug SE** is weather- and chemical resistant.

Technical characteristics

Norm: ISO 1307

Temperature range: -20 °C up to +50 °C

Standard Length: 50 m | from DN 80: 30 m

Colour: Grey with blue spiral

Construction

Cover: PVC, corrugated

Reinforcement: Hard-PVC spiral, impact and pressure resistant

Lining: PVC, smooth

Inner-Ø mm	Inner-Ø Inch	WP bar	BP bar	Vacuum bar	Bending radius mm	Weight/m kg	Article no.
51	2	4	13	0,90	200	0,975	11201-051
76	3	3	10	0,90	310	1,700	11201-076
80	-	3	10	0,90	320	1,800	11201-080
102	4	2	10	0,80	410	2,600	11201-102
127	5	2	7	0,70	520	3,650	11201-127
152	6	1	7	0,70	610	5,100	11201-152

Reliable, for sure!