



GruloHT 175

High temperature hose of Hypalon®

Very lightweight and highly flexible high temperature ducting made of Hypalon®-coated polyester fabric with wear strip. **GruloHT 175** is black on the outside and green inside and has a good temperature-, chemical- as well as UV- and ozone resistance. The hose is flame retarding and has an excellent axial compressibility and a good mechanical strength. It is used especially in the suction of hot and cold fumes, gases and dusts in all fields of industry.

Technical characteristics

Temperature range: -40 °C to +175 °C

Standard Length: 3 m to 10 m

Colour: External: black, internal: green

Construction

Material: Hypalon® coated polyester fabric with outer wear strip

Inner-Ø mm	Material thickness mm	WP bar	Vacuum bar	Bending radius mm	Weight/m kg	Article no.
50	0,40	0,85	0,40	30	0,400	12022-050
60	0,40	0,78	0,28	36	0,480	12022-060
76	0,40	0,60	0,17	45	0,600	12022-076
80	0,40	0,58	0,16	48	0,620	12022-080
102	0,40	0,50	0,10	60	0,650	12022-102
110	0,40	0,48	0,08	66	0,700	12022-110
120	0,40	0,35	0,06	72	0,720	12022-120
127	0,40	0,32	0,06	75	0,800	12022-127
152	0,40	0,22	0,04	90	0,900	12022-152
160	0,40	0,21	0,04	96	0,940	12022-160
180	0,40	0,17	0,03	108	1,050	12022-180
203	0,40	0,15	0,02	120	1,210	12022-203
254	0,40	0,10	0,01	175	1,700	12022-254
305	0,40	0,07	0,01	210	2,130	12022-305
350	0,40	0,06	0,01	245	2,500	12022-350
407	0,40	0,05	0,01	280	3,150	12022-407
508	0,40	0,04	0,01	400	4,150	12022-508

Reliable, for sure!