



GrünLine

GrüloFaekaFlex

Very elastic suction and pressure hose

Very elastic suction and delivery hose with rigid PVC spiral for the use in communal applications, for irrigation and in the agricultural sector. Very good cold flexibility, high resistance against abrasion and many chemicals.

Technical characteristics

Temperature range: -25 °C to +60 °C

Standard Length: 50 m | DN 127: 30 m, DN 152: 20 m, DN 203: 10 m

Colour: Gray, red spiral strip

Construction

Cover: PVC, lightla corrugated

Reinforcement: Rigid PVC spiral, impact and pressure resistant

Lining: PVC, smooth

Inner-Ø mm	Inner-Ø Inch	Outer-Ø mm	WP bar	Vacuum bar	Bending radius mm	Weight/m kg	Article no.
51	2	60,4	6,0	0,85	302	1,030	12072-051
63	2 1/2	73,4	5,5	0,85	367	1,360	12072-063
76	3	87,6	5,0	0,85	438	1,750	12072-076
80	-	91,8	4,5	0,85	459	1,845	12072-080
102	4	115	4,5	0,80	575	2,650	12072-102
127	5	141	3,5	0,80	705	3,540	12072-127
152	6	167,6	3,0	0,80	838	5,000	12072-152
203	8	222,0	2,5	0,80	1.110	8,400	12072-203
254	10	277	2,0	0,80	1.662	10,300	12072-254

All technical information refer to a temperature of 22 °C.

Reliable, for sure!