



GrünloFlex TPE 20

TPE compression air hose 20 bar

GrünloFlex TPE 20 shows similar properties like a rubber hose due to its special Thermorub® composite material. It is very flexible even at low temperatures and oil resistant. Due to the high-strength textile fabric **GrünloFlex TPE 20** is especially suitable as compression air or water hose. Ideal for filling stop-off bags!

Technical characteristics

Norm: ISO 1307

Temperature range: -10 °C to +60 °C

Standard Length: 40 m

Colour: Black with orange stripes

Construction

Cover: TPE, abrasion-, ozone- and weather resistant

Reinforcement: Two high-strength synthetic textile fabric

Lining: TPE, partly oil resistant, black



Inner-Ø mm	Inner-Ø Inch	Wall thickness mm	WP bar	BP bar	Bending radius mm	Weight/m kg	Article no.
6	1/4	3,50	20	60	70	0,155	12228-006
8	5/16	3,50	20	60	90	0,190	12228-008
10	3/8	3,50	20	60	120	0,225	12228-010
13	1/2	4,00	20	60	180	0,335	12228-013
16	5/8	4,50	20	60	205	0,435	12228-016
19	3/4	5,00	20	60	240	0,565	12228-019
25	1	5,50	20	60	300	0,790	12228-025

Reliable, for sure!