



OptiVrac ABR

Flexible suction hose

OptiVrac ABR is a highly flexible and corrugated hose which is ideally suited for the use on sewer cleaning vehicles. Its abrasion resistant inner lining is specially developed for suction excavators with mechanical arm for high abrasive materials as well as for industrial cleaning purposes.

Technical characteristics

Temperature range: -30 °C to +70 °C

Standard Length: 20 m, 25 m, 30 m | DN 252: max. 12 m

Colour: Black

Construction

Cover: SBR, corrugated, with fabric impressions, weathering and abrasion resistant

Reinforcement: High strength synthetic cord, embedded steel wire helix

Lining: Para/NR, black, smooth, abrasion resistant, antistatic

Marking: Transfer tape orange, [G+L-Ellipse] - OptiVrac ABR

Inner-Ø mm	Inner-Ø Inch	WP bar	BP bar	Vacuum bar	Bending radius mm	Weight/m kg	Article no.
80	-	3	9	0,90	245	1,980	12514-080
102	4	3	9	0,90	310	2,630	12514-102
127	5	3	9	0,90	380	3,950	12514-127
152	6	3	9	0,90	460	4,490	12514-152
203	8	3	9	0,90	610	9,980	12514-203
252	10	3	9	0,90	950	18,400	12514-252

Reliable, for sure!