



OptiVrac OIL

Flexible and oil resistant suction hose

OptiVrac OIL is a highly flexible and corrugated hose which is ideally suited for the use on sewer cleaning vehicles. Its abrasion resistant inner lining is specially developed for suction excavators with mechanical arm for high abrasive materials as well as for industrial cleaning purposes.

Technical characteristics

Temperature range: -20 °C to +70 °C

Standard Length: 20 m, 25 m, 30 m

Electrical resistance: Cover $R \leq 10^6 \Omega/m$

Colour: Black

Construction

Cover: SBR, corrugated, with fabric impressions, weathering and abrasion resistant

Reinforcement: High strength synthetic cord and helix wire

Lining: SBR, black, smooth, abrasion resistant, antistatic

Marking: Transfer tape yellow, [G+L-Ellipse] - OptiVrac OIL

Inner-Ø mm	Inner-Ø Inch	WP bar	BP bar	Vacuum bar	Bending radius mm	Weight/m kg	Article no.
80	3 1/4	3	9	0,90	320	2,500	12524-080
102	4	3	9	0,90	410	3,810	12524-102
110	-	3	9	0,90	440	4,390	12524-110
127	-	3	9	0,90	500	4,980	12524-127
152	6	3	9	0,90	610	7,540	12524-152
203	8	3	9	0,90	815	10,430	12524-152

Reliable, for sure!