



GrüloLine

GrüloPipe Flex 1SC EN 857

Streaks-Free

In addition to all benefits of a premium high pressure rubber hose the **GrüloPipe Flex 1SC EN 857** leaves no streaks. The hose is extremely flexible, abrasion-, pressure- and oil resistant. The **GrüloPipe Flex 1SC EN 857** is suited perfectly for the application on jetting lances, used in the food industry like the cleaning of slaughterhouses, hallways etc..

All hoses are assembled with ferrules on both sides in accordance with their respective requirements. Delivery takes place with test certificate to EN 10 204.3.1 B on each assembled hose.

Technical characteristics

Norm: EN 857

Temperature range:

-40 °C up to +100 °C for hydraulic oils mineral-based

-40 °C up to +70°C for hydraulic oils water-based

±0 °C up to +70°C for water

Standard Length: 40 m, 60 m, 80 m, 120 m

Availability: 40 m up to 120 m

Colour: Grey

Construction

Cover: SBR, smooth

Reinforcement: Steel wire braid

Lining: SBR, smooth

Marking: G+L EN 857 1 SC DN [...] WP 200 bar



Inner-Ø mm	Inner-Ø Inch	Wall thickness mm	WP bar	BP bar	Bending radius mm	Weight/m kg	Article no.
13	1/2	4,00	200	800	70	0,350	12550-013
16	5/8	3,70	130	650	90	0,430	12550-016
19	3/4	4,00	105	520	100	0,510	12550-019

Reliable, for sure!