

Schneckengewindeschelle Typ L / 9 mm | W2



Technische Merkmale in der Übersicht

Norm: DIN 3017

Material: Edelstahl X6Cr17 | DIN 1.4016

Schraubenmaterial: Stahl QST 36-3 weiß verzinkt Cr3 | DIN 1.0213

Spannbereich mm	Bandbreite mm	Drehmoment Nm	Betriebsdruck bar	Artikel-Nr.
8 – 12	9,0	1,5	40	30000-W2-09-012
8 – 16	9,0	3,0	45	30000-W2-09-016
12 – 22	9,0	3,0	45	30000-W2-09-022
16 – 27	9,0	3,5	42	30000-W2-09-027
20 – 32	9,0	3,5	36	30000-W2-09-032
20 – 35	9,0	4,0	34	30000-W2-09-035
25 – 40	9,0	4,0	32	30000-W2-09-040
30 – 45	9,0	4,0	28	30000-W2-09-045
32 – 50	9,0	4,0	24	30000-W2-09-050
40 – 60	9,0	4,0	19	30000-W2-09-060
50 – 70	9,0	4,0	17	30000-W2-09-070
60 – 80	9,0	4,0	15	30000-W2-09-080
70 – 90	9,0	4,0	13	30000-W2-09-090
80 – 100	9,0	4,0	11	30000-W2-09-100
90 – 110	9,0	4,0	10	30000-W2-09-110
100 – 120	9,0	4,0	9	30000-W2-09-120
110 – 130	9,0	4,0	8	30000-W2-09-130
120 – 140	9,0	4,0	7	30000-W2-09-140
130 – 150	9,0	4,0	6	30000-W2-09-150
140 – 160	9,0	4,0	5	30000-W2-09-160

Auch in W1, W4 und W5 lieferbar!